

KLONDIKE

TWIN MOVING TABLE MULTI-CHANNEL MULTI-SPINDLE

Standard Features

- + Fagor 8065 Power HMI Elite
- + Fagor Quercus Servo Drives
- + Upgraded to Fagor FKM 64 on X and Y axis for Optimal Performance
- + Rack and Pinion on X and Y axes, Z axis Ball Screw with Brake Motors
- + (2) Hiteco Powertech 400 - 13Kw (S1), 24,000 RPM Max. Speed, HSK 63F, Liquid Cooled, VFD Drives

Benefits

- + Unparalleled Production per Square Unit of Floor Space
- + More Rigidity, Higher Feedrates, Greater Acceleration
- + Flexibility: Run Two Different Programs at the Same Time or Pendulum Process with Two Spindles Simultaneously
- + Touch Screen Configurable for Ease of Use

Machine Specs

- + Accommodates All Common Panel Sizes
- + Table Configurations: Single: 5x10, 5x8 Twin: 5x8, 5x10, 5x6
- + Rapid Feedrates: X/Y 2000 IPM Z 1000 IPM
- + 8 station tool carousel per carriage
- + 8" max tool length
- + Z Stroke 18"
- + Z clearance 18"
- + 2 to 4 carriage configurations available

